

**for screw-machined contacts**

**Features**

- 8 indent Crimp to Military standard
- Ratchet mechanism ensures complete crimp cycle
- 8 Position Dial select Indent Depth control
- Many Turrets / Positioners available
- Ergonomic non-slip handles
- Widely used in Aerospace and Military applications

**Compatible**

**Tyco Electronics contacts**

Screw-machined contacts in loose piece form

All of the tools give a concentric circular crimp configuration required by certain shielded contacts to insure compatibility with connector inserts and installing or removal tools.



Insertion and extraction tools, positioners, inspection gages, and other accessories are available for these tools upon request.

**Hand Tool AF8**

**Base Tool**  
without Turret  
**PN 0-0601967-1**  
MIL-C-22520/1-01

**Turret TH1A**  
Wire Size Range  
0.2-4.0 mm (AWG 24-12)  
**PN 0-0161967-2**

**Turret TH 501  
for Type II contacts**  
Wire Size Range  
0.03 - 2.5 mm (AWG 32-14)  
**PN 1-0601967-5**

**AF8 Turret TH502  
for Type II contacts**  
Wire Size Range  
0.03 - 2.5 mm (AWG 32-14)  
**PN 1-0601967-6**

**Hand Tool AFM8**

**Base Tool**  
without Positioner  
**PN 0-0601966-1**  
MIL-C-22520/2-01

**Positioner K 41**  
Wire Size Range  
0.4 mm (AWG 22)  
Meets MIL-C-22520/2-06  
**PN 601966-4**

**Positioner K13-1**  
Meets MIL-C-22520/2-C8  
Wire Size Range  
0.56 mm (AWG 20)  
**PN 0-0601966-5**

**Positioner K 42**  
Meets MIL-C-22520/2-09  
Wire Size Range  
0.4 mm (AWG 22)  
**PN 0-0601966-6**

**Hand Tool M310**

**Base Tool**  
without Positioner  
**PN 0-0356114-1**

**Positioner TP 1013**  
Wire Size Range  
2.5 - 6.0 mm (AWG 14-10)  
**PN 0-0356337-1**